

Safety Data Sheet




ULTRAPLAN RENOVATION

Safety Data Sheet dated 1/12/2012, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Trade name: ULTRAPLAN RENOVATION
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Cement based levelling mortar.
Uses advised against: ==
- 1.3. Details of the supplier of the safety data sheet
Supplier:
MAPEI U.K. Ltd - Mapei House Steel Park Road
Halesowen - West Midlands B62 8HD
Competent person responsible for the safety data sheet:
sicurezza@mapei.it
- 1.4. Emergency telephone number
MAPEI U.K. Ltd - phone: +44(0)121 508 6970
fax: +44(0)121 5086 960
www.mapei.co.uk (office hours)

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:
Properties / Symbols:
 Xi Irritant
- R Phrases:
R43 May cause sensitization by skin contact.
- Adverse physicochemical, human health and environmental effects:
No other hazards
- 2.2. Label elements
- 
- ^{Xi}
Symbols:
 Xi Irritant
- R Phrases:
R43 May cause sensitization by skin contact.
- S Phrases:
S22 Do not breathe dust.
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- Contents:
Portland cement, Cr(VI) < 2 ppm
- Special provisions according to Annex XVII of REACH and subsequent amendments:
None
- 2.3. Other hazards

900124351/1

Page n. 1 of 10

Safety Data Sheet

ULTRAPLAN RENOVATION

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

See at paragraph 11 the additional information concerning crystalline silica

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and corresponding classification:

25% - 50% free crystalline silica ($\varnothing > 10 \mu$)

CAS: 14808-60-7, EC: 238-878-4

2.5% - 5% Portland cement, Cr(VI) < 2 ppm

CAS: 65997-15-1, EC: 266-043-4

Xi; R41-43-37/38

348 $\mu\text{g}/\text{kg}$ acetato di vinile

REACH No.: 01-2119471301-50-XXXX, Index number: 607-023-00-0, CAS: 108-05-4, EC: 203-545-4

F, Carc. Cat. 2, Xn, Xi; R20-11-40-37

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.6/2 Carc. 2 H351

⚠ 3.1/4 Inhal Acute Tox. 4 H332

⚠ 3.8/3 STOT SE 3 H335

228 $\mu\text{g}/\text{kg}$ acetaldehyde; ethanal

Index number: 605-003-00-6, CAS: 75-07-0, EC: 200-836-8

F+, Carc. Cat. 3, Xi; R12-36/37-40

⚠ 2.6/1 Flam. Liq. 1 H224

⚠ 3.6/2 Carc. 2 H351

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

34 $\mu\text{g}/\text{kg}$ methanol

Index number: 603-001-00-X, CAS: 67-56-1, EC: 200-659-6

F, T; R11-23/24/25-39/23/24/25

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.8/1 STOT SE 1 H370

⚠ 3.1/3 Oral Acute Tox. 3 H301

⚠ 3.1/3 Dermal Acute Tox. 3 H311

⚠ 3.1/3 Inhal Acute Tox. 3 H331

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Safety Data Sheet

ULTRAPLAN RENOVATION

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

If brought into contact with the skin, the product may cause sensitisation of the skin.

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

The product does not present a fire hazard

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Rapidly recover the product, wearing protective clothing.

Scoop into containers and seal for disposal.

After the product has been recovered, rinse the area and materials involved with water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes and exposure to high dust concentration.

Avoid powder development and deposit

Contaminated clothing should be changed before entering eating areas.

Safety Data Sheet

ULTRAPLAN RENOVATION

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.

Incompatible materials:

Keep away from water or from damp surroundings.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

free crystalline silica ($\text{Ø} > 10 \mu$) - CAS: 14808-60-7

TLV TWA: - 0,025 mg/m³ (respirable fraction)

Portland cement, Cr(VI) < 2 ppm - CAS: 65997-15-1

TLV TWA: - (polvere) 10 mg/m³

acetato di vinile - CAS: 108-05-4

ACGIH - LTE mg/m³: 35.21 mg/m³, 10 ppm - STE mg/m³: 52.82 mg/m³, 15 ppm

NDS - LTE mg/m³: 10 mg/m³

NDSch - LTE mg/m³: 30 mg/m³

EU - LTE mg/m³: 17.6 mg/m³, 5 ppm - STE mg/m³: 35.2 mg/m³, 10 ppm

AGW - LTE mg/m³: 18 mg/m³, 5 ppm

acetaldehyde; ethanal - CAS: 75-07-0

TLV TWA: - A3

TLV STEL: - C 25 ppm - C 45,04 mg/m³, A3

VLE 8h - POLAND (NDS) 5 mg/m³; (NDSP) 45 mg/m³

methanol - CAS: 67-56-1

ACGIH - LTE mg/m³: 262.09 mg/m³, 200 ppm - STE mg/m³: 327.61 mg/m³, 250 ppm

SUVA - LTE mg/m³: 260 mg/m³, 200 ppm - STE mg/m³: 1040 mg/m³, 800 ppm

NDS - LTE mg/m³: 100 mg/m³

NDSch - LTE mg/m³: 300 mg/m³

EU, 200 ppm, 250 ppm

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Safety goggles.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Not needed for normal use.

A dust mask (P2) should be worn if above exposure limits

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Safety Data Sheet

ULTRAPLAN RENOVATION

Thermal Hazards:
None
Environmental exposure controls:
None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	powder
Colour:	grey
Odour:	slight, typical of cement
Odour threshold:	N.A.
pH:	N.A.
pH(water dispersion,10%):	12
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	== °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.1 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	partly soluble
Solubility in oil:	insoluble
Viscosity:	N.A.
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects

900124351/1

Page n. 5 of 10

Safety Data Sheet

ULTRAPLAN RENOVATION

Route(s) of entry:

Ingestion: Yes
Inhalation: Yes
Contact: No

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

acetato di vinile - CAS: 108-05-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 7440 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 15810 mg/m³ - Duration: 4h

b) skin corrosion/irritation:

Test: Skin Irritant - Species: Rabbit Negative - Source: OECD 404

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Rat Negative - Source: OECD 429

e) germ cell mutagenicity:

Test: Mutagenesis Negative - Source: OECD 471

f) carcinogenicity:

Test: Carcinogenicity - Route: Inhalation - Species: Rat Negative 176 mg/m³ - Source: NOAEC

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.

Eye:

The product can cause irritation by contact

Sensitizing Properties:

Frequent and prolonged skin contacts with cement paste may cause dermatitis.

Cancerogenic Effects:

The IARC (International Agency for Research on Cancer) believes that the crystalline silica inhaled at the workplace can cause lung cancer in man.

However, it also points out that the cancer effect depends on the silica characteristics and on the biological-physical condition of the environment.

There is a large amount of information in support of the fact that increased risk of cancer is limited to persons suffering from silicosis.

In the current situation of studies, protection of workers from silicosis can be ensured by respecting the exposure limit values.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause

Safety Data Sheet

ULTRAPLAN RENOVATION

erythema and edema.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Not available data on the mixture

Adopt good industrial practices, so that the product is not released into the environment.

acetato di vinile - CAS: 108-05-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 12.6 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 12.7 mg/l - Duration h: 72

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of hardened product (EC waste code) : 17 01 01

Disposal of not hardened product (EC waste code) : 17 01 01

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

14.1. UN number

UN Number: ==

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

Rail/Road(RID/ADR): no dangerous good

ADR-Upper number: NA

Air (ICAO/IATA): no dangerous good

Safety Data Sheet

ULTRAPLAN RENOVATION

Sea (IMO/IMDG):	no dangerous good
N.A.	
14.4. Packing group	
N.A.	
14.5. Environmental hazards	
ADR Environmental Pollutant:	
Marine pollutant:	No
N.A.	
14.6. Special precautions for user	
N.A.	
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
No	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
 Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
 Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)
 Dir. 98/24/EC (Risks related to chemical agents at work)
 Dir. 2000/39/EC (Occupational exposure limit values)
 Dir. 2006/8/EC
 Regulation (EC) n. 1907/2006 (REACH)
 Regulation (EC) n. 1272/2008 (CLP)
 Regulation (EC) n. 790/2009 (ATP 1 CLP)
 Regulation (EU) n. 453/2010 (Annex I)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

REACH Regulation (1907/2006)

REACH Regulation (1907/2006) – All. XVII

The product contains Cr (VI) under the limitse established by annex. XVII pt.47. Respect the duration according to the information described on the packaging

REACH Regulatio n° 1907/2006 (REACH) – Art. 59 (Substances in “Candidate List”): N.A.

CLP Regulation n° 1272/2008 (CLP) and s.m.i.

Directive n° 1999/45/CE (Dangerous Preparation) and s.m.i.

Directive n° 67/548/CEE (Substances) and s.m.i.

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

Directive 105/2003/CE (Seveso III): N.A.

ADR Agreement – IMDG Code – IATA Regulation

Wassergefährdungsklasse:

VOC (2004/42/EC) : N.A. g/l

Safety Data Sheet

ULTRAPLAN RENOVATION

Social Dialogue on Respirable Crystalline Silica

On April 26, 2006 was signed a multi-sector social dialogue, based on a "Guide to Good Practices", on workers health protection who are in contact with products containing crystalline silica. The text of the agreement published in G.U. European Union (2006 / C 279/02) and the "Guide to Good Practices", with attachments, are available on www.nepsi.eu website, they offer guidelines and useful information for handling products containing respirable crystalline silica.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
- R36/37 Irritating to eyes and respiratory system.
- R37 Irritating to respiratory system.
- R37/38 Irritating to respiratory system and skin.
- R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
- R40 Limited evidence of a carcinogenic effect.
- R41 Risk of serious damage to eyes.
- R43 May cause sensitization by skin contact.

- H225 Highly flammable liquid and vapour.
- H351 Suspected of causing cancer.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H224 Extremely flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H370 Causes damage to organs.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H331 Toxic if inhaled.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- NIOSH - Registry of toxic effects of chemical substances
- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX'S - Dangerous properties of industrial materials
- Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

Safety Data Sheet

ULTRAPLAN RENOVATION

DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	