


Unit 75, Whitehill & Bordon Enterprise Park Budds Lane, Bordon, Hampshire GU35 0FJ

Email: sales@polymax.co.uk Tel: +44 (0)1420 474 123





Maximum Load: 44 Tonnes

Rubber Wheel Chock Solid 235L x 205W x 160H

Product SKU: 6008801

Our selection of standard rubber wheel chocks suitable for various vehicles from caravans, car trailers, heavy goods vehicles and more.

Collection of wheel chocks made entirely from a hardwearing blend of SBR/NR rubber. They offer a longer service life in comparison to plastic alternatives but are a lot heavier to handle. Each chock comes with either an eye bolt, handle or rope to make help make handling easier. The 6008800 and 6008801 use the same design but the 6008801 features a hollow core to reduce the weight and cost.

Colour: Black

Material: NR/SBR

Operating temperature range: -15°C to 70°C

Physical Property	Unit	Typical Values
Hardness	ShA	75
Elongation at Break	%	200
Tensile Strength	MPa	4
Weight	KG	5.2

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. All sales subject to our standard terms www.polymax.co.uk/sales-terms