


Unit 75, Whitehill & Bordon Enterprise Park Budds Lane, Bordon, Hampshire GU35 0FJ

Email: sales@polymax.co.uk Tel: +44 (0)1420 474 123







TyreCord Wheel Chock 254L x 185W x 200H

Product SKU: 6010930

Tyre Cord Hi-Fibre is an extremely tough rubber compound made with nylon or rayon reinforcing fibres.

The toughest HGV wheel chock we offer. This standard sized design is made from 100% solid TPX or Tyre Cord Hi-Fibre rubber. This item has an integrally moulded horizonal handle with a moulded hole to take a shackle to fix a chain or rope. Safety notice - Only select the appropriate wheel chock according to the type and size of your vehicle. Wheel chocks should be used in pairs and applied only when the vehicle has come to a complete standstill. It is paramount the end user tests the product and ensures it is suitable for the application requirement.

Colour: Black

Material: TyreCord Hi-Fibre

Operating temperature range: -15°C to 70°C

Physical Property	Unit	Typical Values
Hardness	ShA	78
Elongation at Break	%	15
Tensile Strength	MPa	3.4
Weight	KG	4.4

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. All sales subject to our standard terms www.polymax.co.uk/sales-terms