



VF Range of Height Adjustable and Articulated Machinery Mount

The VF mounts are used for levelling and support, it in many applications including lathes, milling machines, machining centres and conveyor systems.

The base rubber is made of oil resistant NBR, with the stainless-steel versions being commonly used in the food industry.

Product Code	A (mm)	B (mm)	D (mm)	F	G (mm)	H (mm)	Static Load kg	Metal type	Articulation Degrees
VF6022M14100-2	19	100	63	M14	11.5	119	1800	MS	5
VF8025M12120-A4-2	35	125	80	M14	12	25	1000	A4	10
VFM5011M12100-2	19	100	50	M12	11.5	119	1500	MS	5
VF8025M12150-2	35	150	80	M12	25	85	1000	MS	10
VF10028M16150-2	37.5	150	100	M16	28	187.5	1500	MS	10
VF5019M10100-2	29	100	50	M10	19	129	400	MS	10
VF12032M16150-2	41.5	100	120	M16	32	191.5	3000	MS	10
VF8025M12125-A4-2	38	125	80	M16	25	163	1000	A4	10
VF8035M16150-2	35	150	80	M16	25	185	1000	MS	10
VF6032M10100-A4-2	32	100	60	M10	22	132	700	A4	10
FPS80M16125	31	125	100	M16	28	156	900	MS	5

MS - Mild Steel A4- SS304 Stainless Steel

NBR 80 Shore A Rubber Pads

Load values above mentioned are to be considered using static conditions and are calculated at half of the screw length. In presence of dynamic loads these values should be suitably reduced (please consult our selection guide for details)

These feet satisfy REACH and RoHS regulations.

